


Raychem Dry Compact Switchgear &
Transformer Termination PHVS & PHVT
up to 245 kV

Raychem
from TE Connectivity

Raychem Dry Compact Switchgear & Transformer Termination PHVS & PHVT up to 245 kV



Application

The dry compact switchgear termination for voltage classes up to 245 kV is designed to be installed in cable entry housings of gas-insulated switchgear (GIS). It complies with IEC 62271-209 standard, which essentially specifies the interfaces between the termination and the switchgear. Therefore the termination will fit into all GIS complying with IEC 62271-209. Adapters are available to match the dimensions of wet (oil-filled) type terminations, and older designs specified in IEC 60859. The termination operates in SF₆ but also in insulating liquids like transformer oil. A corona shield at the top of the termination then provides the necessary shielding of the terminal. The termination is easily separable and consists of a plug-in part and an epoxy resin insulator. The insulator can be installed by the GIS or transformer manufacturer already at the factory saving installation time on-site and

reducing the risk of contamination of the cable entry housing. In case of short cable links and due to the short length and light weight of the plug-in part it can be also pre-installed by the cable manufacturer further reducing the time required to install a substation.

Features

- Dry interfaces, no oil-filling
- Dimensions comply with IEC 62271-209
- Pressure-tight resin housing
- Operates in SF₆ and insulating liquids
- Pre-fabricated and factory tested Si-rubber stress cone
- Torque-controlled or wedge-type multi-contact conductor bolt
- No special tools required to install the termination
- Isolated cable gland for sectionalization
- Type tested according to IEC 60840, IEC 62067 and IEC 62271-209 standards

Major Design Elements

The epoxy-resin insulator (4) with embedded multi-contact electrode forms the gas pressure-tight interface between GIS or transformer cable entry and the plug-in part of the termination. It is attached to the cable entry housing with the fixing ring (7). The torque-controlled shear-off bolt connector (3) with multi contacts fits the cable conductor. The connector is suitable for stranded aluminium and copper conductors and can be modified to accept solid conductors as well. No special tool is required to install the connector. The silicone rubber stress cone (5) provides the electrical field control and can easily be applied without tools owing to its excellent elasticity. A metal spring-loaded compression ring (6) presses the rubber stress cone into the specially shaped interior of the resin housing, ensuring a uniform contact pressure and electrically sound interface. A corona shield (1) can be easily attached to the termination for use in insulating liquids. Compared with IEC 62271-209 wider clearances apply in this application. The cable outer serving is adapted through a gland system (8), which addresses the individual shielding and armouring. The gland system also secures the cable. An adapter (2) can be used to match the dimensions of wet type switchgear and transformer terminations which makes the termination the ideal choice for replacing oil-filled terminations.

- 1 Corona shield (PHVT only)
- 2 Adapter (optional)
- 3 Mechanical connector
- 4 Resin housing

- 5 Stress cone
- 6 Spring-loaded compression ring
- 7 Fixing ring
- 8 Gland and sealing

While TE Connectivity (TE) has made every reasonable effort to ensure the accuracy of the information in this catalog, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this catalog are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications. Raychem, TE Connectivity and TE Connectivity (logo) are trademarks. Other logos, product and company names mentioned herein may be trademarks of their respective owners.

TE Energy - innovative and economical solutions for the electrical power industry: cable accessories, connectors & fittings, insulators & insulation, surge arresters, switching equipment, street lighting, power measurement and control.

Tyco Electronics Raychem GmbH
a TE Connectivity Ltd. Company
TE Energy
Finsinger Feld 1
85521 Ottobrunn/Munich, Germany

Phone: +49-89-6089-0
Fax: +49-89-6096345

energy.te.com

